DOVER GREENS


DOVER GREENS, LLC 207 HUTCHINSON AVE., WINGDALE, NY 12594

UTILITY SERVICE & DISTRIBUTION PLAN PHASE I




SCHEDULE OF DRAWINGS:


SHEET NO.	DRAWING NO.	TITLE
1	TS	TITLE SHEET
2	PH-001	PHASING PLAN
3	ES-001	LEGEND & NOTES
4	ES-002	ELECTRICAL SUPPLY- SITE PLAN (FULL BUILD)
5	ES-003	FIBER OPTIC DATA - SITE PLAN (FULL BUILD)
6	ES-004	NATURAL GAS SUPPLY - SITE PLAN (FULL BUILD
7	ES-101	PHASE 1 UTILITIES SUPPLY PLAN
8	ES-111	PHASE 1 PARTIAL SITE PLAN
9	ES-112	PHASE 1 PARTIAL SITE PLAN
10	ES-113	PHASE 1 PARTIAL SITE PLAN
11	ES-114	PHASE 1 PARTIAL SITE PLAN
12	ES-115	PHASE 1 PARTIAL SITE PLAN
13	ES-116	PHASE 1 PARTIAL SITE PLAN
14	ES-117	PHASE 1 PARTIAL SITE PLAN
15	ES-118	PHASE 1 PARTIAL SITE PLAN
16	ES-102	PHASE 1 SWITCHING LAYOUT & SCHEDULES
17	ES-701	SITE UTILITY DETAILS
18	ES-702	SITE UTILITY DETAILS
19	ES-703	SITE UTILITY DETAILS



File Name: C:\Users\sar\appdata\local\temp\AcPublish_5568__TS-PHASE 1.dwg (Layout: La Date: Tue, Jul 19, 2016 - 3:31 PM (Name: sar)




TRENCH & TRENCH RESTORATION FOR TRENCH OPENINGS IN GRASSED AREA N.T.S.



- IN AREAS WHERE PAVEMENT IS REMOVED FOR TRENCHING, CONTRACTOR SHALL NEATLY SAW-CUT PAVEMENT THROUGH ASPHALTIC LAYERS PRIOR TO REMOVAL, AS NOTED ABOVE
- 2. EXISTING PAVEMENT THAT IS SAW-CUT SHALL BE COATED AND SEALED ALONG ALL CUTS PRIOR TO INSTALLATION OF MATERIALS NEXT TO THE PAVEMENT

TRENCH & TRENCH RESTORATION FOR TRENCH OPENINGS IN PAVEMENT



CROSS SECTION

TRENCH & TRENCH RESTORATION FOR TRENCH OPENINGS IN SIDEWALKS

E&S NOTES:

- 1. THE OPERATOR SHALL ASSURE THAT THE APPROVED EROSION AND SEDIMENT CONTROL PLAN IS PROPERLY AND COMPLETELY IMPLEMENTED.
- 2.CONSTRUCTION VEHICLES AND EQUIPMENT ENTERING AND EXITING THE SITE MUST ENTER AND EXIT AT THE STABILIZED CONSTRUCTION ENTRANCE LOCATION(S) ONLY. MEASURES MUST BE TAKEN TO PREVENT SOIL AND SEDIMENT FROM A VEHICLE'S TIRES FROM BEING DEPOSITED ONTO THE PUBLIC ROADS.
- 3.UNTIL THE SITE ACHIEVES FINAL STABILIZATION, THE OPERATOR SHALL ASSURE THAT THE BEST MANAGEMENT PRACTICES ARE IMPLEMENTED, OPERATED, AND MAINTAINED PROPERLY AND COMPLETELY. MAINTENANCE SHALL INCLUDE INSPECTIONS OF ALL BEST MANAGEMENT PRACTICE FACILITIES. THE OPERATOR WILL MAINTAIN AND MAKE AVAILABLE TO THE TOWN OF DOVER COMPLETE, WRITTEN INSPECTION LOGS OF ALL THOSE INSPECTIONS. ALL MAINTENANCE WORK, INCLUDING CLEANING, REPAIR, REPLACEMENT, REGRADING, AND RESTABILIZATION SHALL BE PERFORMED IMMEDIATELY.
- 4.IMMEDIATELY UPON DISCOVERING UNFORESEEN CIRCUMSTANCES POSING THE POTENTIAL FOR ACCELERATED EROSION AND/OR SEDIMENT POLLUTION, THE OPERATOR SHALL IMPLEMENT APPROPRIATE BEST MANAGEMENT PRACTICES TO ELIMINATE POTENTIAL FOR ACCELERATED EROSION AND/OR SEDIMENT POLLUTION.
- 5.BEFORE INITIATING ANY REVISIONS TO THE APPROVED EROSION AND SEDIMENT CONTROL PLAN OR REVISIONS TO OTHER PLANS THAT MAY AFFECT THE EFFECTIVENESS OF THE APPROVED E&S CONTROL PLAN, THE OPERATOR MUST RECEIVE APPROVAL OF THE REVISIONS FROM THE TOWN OF DOVER.
- 6. THE OPERATOR SHALL ASSURE THAT AN EROSION AND SEDIMENT CONTROL PLAN HAS BEEN PREPARED, APPROVED BY THE TOWN OF DOVER, AND IS BEING IMPLEMENTED AND MAINTAINED FOR ALL SOIL AND/OR ROCK SPOIL AND BORROW AREAS. REGARDLESS OF THEIR LOCATIONS.
- 7.A COPY OF THE APPROVED EROSION AND SEDIMENT CONTROL PLAN MUST BE AVAILABLE AT THE PROJECT SITE AT ALL TIMES.
- 8.THE E&S CONTROL PLAN MAPPING MUST DISPLAY A NY ONE CALL SYSTEM INCORPORATED SYMBOL INCLUDING THE SITE IDENTIFICATION NUMBER. (THIS IS A NUMBERED SYMBOL NOT A NOTE.)
- 9. EROSION AND SEDIMENT BMPS (BEST MANAGEMENT PRACTICES) MUST BE CONSTRUCTED, STABILIZED, AND FUNCTIONAL BEFORE SITE DISTURBANCE BEGINS WITHIN THE TRIBUTARY AREAS OF THOSE BMPS.
- 10.IMMEDIATELY AFTER EARTH DISTURBANCE ACTIVITIES CEASE, THE OPERATOR SHALL STABILIZE ANY AREAS DISTURBED BY THE ACTIVITIES. DURING NON-GERMINATING PERIODS, MULCH MUST BE APPLIED AT THE SPECIFIED RATES. DISTURBED AREAS WHICH ARE NOT AT FINISHED GRADE AND WHICH WILL BE REDISTURBED WITHIN 1 YEAR MUST BE STABILIZED IN ACCORDANCE WITH THE TEMPORARY VEGETATIVE STABILIZATION SPECIFICATIONS. DISTURBED AREAS WHICH ARE AT FINISHED GRADE OR WHICH WILL NOT BE REDISTURBED WITHIN 1 YEAR MUST BE STABILIZED IN ACCORDANCE WITH THE PERMANENT VEGETATIVE STABILIZATION SPECIFICATIONS.
- 11.UNTIL THE SITE IS STABILIZED, ALL EROSION AND SEDIMENT BMPS MUST BE MAINTAINED PROPERLY. MAINTENANCE MUST INCLUDE INSPECTIONS OF ALL EROSION AND SEDIMENT CONTROL BMPS AFTER EACH RUNOFF EVENT AND ON A WEEKLY BASIS. ALL PREVENTATIVE AND REMEDIAL MAINTENANCE WORK, INCLUDING CLEAN OUT, REPAIR, REPLACEMENT, REGRADING, RESEEDING, REMULCHING, AND RENETTING, MUST BE PERFORMED IMMEDIATELY. IF EROSION AND SEDIMENT CONTROL BMPS FAIL TO PERFORM AS EXPECTED, REPLACEMENT BMPS, OR MODIFICATIONS OF THOSE INSTALLED WILL BE REQUIRED.
- 12.SEDIMENT REMOVED FROM BMPS SHALL BE DISPOSED OF IN LANDSCAPED AREAS OUTSIDE OF STEEP SLOPES, WETLANDS, FLOODPLAINS OR DRAINAGE SWALES AND IMMEDIATELY STABILIZED, OR PLACED IN TOPSOIL STOCKPILES
- 13.THE OPERATOR SHALL REMOVE FROM THE SITE, RECYCLE, OR DISPOSE OF ALL BUILDING MATERIALS AND WASTES IN ACCORDANCE WITH ALL APPLICABLE STATE AND LOCAL CODES. THE CONTRACTOR SHALL NOT ILLEGALLY BURY, DUMP, OR DISCHARGE ANY BUILDING MATERIAL OR WASTES AT THE SITE.

BMPS - AFTER DISTURBANCE

- 1. WITHIN FOURTEEN (14) DAYS OF ACHIEVING FINAL SITE STABILIZATION. TEMPORARY EROSION AND SEDIMENT BMPS CONTROLS MUST BE REMOVED. AREAS DISTURBED DURING REMOVAL OF THE BMPS MUST BE STABILIZED IMMEDIATELY.
- 2.AN AREA SHALL BE CONSIDERED TO HAVE ACHIEVED FINAL STABILIZATION WHEN IT HAS A MINIMUM UNIFORM 70% PERENNIAL VEGETATIVE COVER OR OTHER PERMANENT NON-VEGETATIVE COVER WITH A DENSITY SUFFICIENT TO RESIST ACCELERATED SURFACE EROSION AND SUBSURFACE CHARACTERISTICS SUFFICIENT TO RESIST SLIDING AND OTHER MOVEMENTS.

LAWN RESTORATION SCHEDULE & NOTES

	SPECIES	LBS / 1,000 SQFT
	TALL FESCUE	1
PERMANENT SEED MIXTURE	KENTUCKY BLUEGRASS	3
	PERENNIAL RYEGRASS	1

- NOTE: OPTIMUM PERMANENT SEEDING SCHEDULE: SPRING OR EARLY FALL
- REMOVE ALL DEBRIS (STICKS, STONES, ETC.) FROM AREA, AND PREPARE SOIL BY TILLING TO A 3"-4" DEPTH.
- 2. RAKE SURFACE LEVEL TO PREVENT WATER FROM POOLING IN ONE AREA. AREAS LOCATED ON A SLOPE SHALL BE RAKED PARALLEL WITH CONTOURS TO PREVENT MOISTURE RUN-OFF.
- 3. FERTILIZER SHALL BE APPLIED TO THE TILLED SOIL AT RATE OF 6 LBS. PER 1,000 sq.ft. FERTILIZER SHALL BE A COMMERCIAL 10-0-10 MIXTURE.
- 4. AREA SHALL BE LIGHTLY SPRAYED WITH WATER TO ALLOW SOIL TO SETTLE.
- 5. PERMANENT SEED MIXTURE SHALL BE SPREAD BY HAND, LAWN SPREADER OR MECHANICAL SEEDER (AS APPROPRIATE FOR SIZE OF AREA) AT A RATE OF 5 lbs. OF SEED MIXTURE PER 1,000 sq.ft. DO NOT OVERSEED, OR OVER CROWDING OF THE SEEDLINGS MAY OCCUR, AND HAMPER PROPER LAWN
- 6. LIGHTLY COVER SEEDED AREA WITH $\frac{1}{4}$ " OF SOIL. (ROLLING OF SEEDBED TO PROMOTE SOIL TO SEED CONTACT IS OPTIONAL.) AND COVER WITH A MULCH OF HAY OR STRAW AT A RATE OF 90 lbs (APPROX 2 BALES) PER 1,000 sq.ft.
- 7. SEEDED AREA SHALL BE COVERED WITH A MULCH OF STRAW OR HAY AT THE RATE OF 90 lbs. (APPROX. 2 BALES) PER 1,000 S.F. TO HELP MAINTAIN SOIL MOISTURE LEVEL.
- 8. LIGHTLY WATER SEED BED DAILY TO KEEP IT MOIST, WHILE TAKING CARE NOT TO SATURATE.


9. NEW GRASS SHALL NOT BE MOWED UNTIL IT HAS REACHED A MINIMUM HEIGHT OF 2"-2½".


10. PRACTICE REGULAR MAINTENANCE & WATER REGULARLY AS CONDITIONS REQUIRE.


SITE - ELECTRICAL: GENERAL NOTES:

- CONTRACTOR SHALL ABIDE BY THEIR OWN EXPENSE TO THE LATEST EDITIONS OF ALL OSHA REGULATIONS AND REQUIREMENTS.
- 2. THERE SHALL BE NO CLAIMS AGAINST THE OWNER FOR WORK STOPPAGES DUE TO ACTS OF GOD, WEATHER CONDITIONS, STOP WORK ORDERS (VERBAL AND/OR WRITTEN), UNDERESTIMATION OF WORK, ESTIMATED QUANTITIES, MATERIALS, SUPPLIES, TOOLS, CORRECTION OF SAFETY PROBLEMS, OR ANY OTHER REASON.
- 3. ALL QUANTITIES SHOWN ON THE DRAWING ARE ESTIMATED QUANTITIES ONLY. IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO FIELD VERIFY AND ASCERTAIN ALL EXISTING CONDITIONS, DIMENSIONS AND QUANTITIES.
- 4. ALL WORK SHALL BE PERFORMED BY THOSE WHO ARE SKILLED IN THEIR TRADE, JOURNEYMEN MECHANICS, TO PRODUCE A FIRST CLASS JOB. THE CONTRACTOR IS ADVISED THAT WORK DEEMED UNSUITABLE, UNACCEPTABLE, SECOND CLASS IN NATURE BY THE PROJECT ENGINEER SHALL BE DEEMED NON-ACCEPTABLE AND THE CONTRACTOR SHALL REMOVE, REPLACE, RE-DO, TO THE SATISFACTION OF THE OWNER, THE UNACCEPTABLE WORK AT NO ADDITIONAL COST TO THE OWNER. THERE SHALL BE NO ADDITIONAL CLAIMS AGAINST THE OWNER FOR THE ABOVE.
- 5. ROAD WAYS, BUILDING EMERGENCY ACCESS AREAS, AND BUILDING ENTRY AND EXITS AREAS ARE TO BE KEPT CLEAR AT ALL TIMES.
- 6. CONTRACTOR SHALL USE DIG SAFELY NY "DIAL 811".
- 7. CONTRACTOR SHALL BE RESPONSIBLE TO VERIFY AND ASCERTAIN IN THE FIELD, ALL EXISTING UTILITIES, EXISTING CONDITIONS, FIELD MEASUREMENTS, DIMENSIONS, AND QUANTITIES, RELATED TO THE PROJECT.
- 8. THE CONTRACTOR SHALL BE RESPONSIBLE TO VERIFY AND ASCERTAIN THE LOCATION, DEPTH, DIRECTION, AND SIZE, OF ANY AND ALL UTILITIES EXISTING IN THE GENERAL VICINITY OF THE WORK AREA.
- 9. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO REPAIR ANY UTILITY DISRUPTED, BROKEN, OR OTHERWISE RENDERED NON-FUNCTIONAL DUE TO THE WORK PERFORMED AT NO ADDITIONAL COST TO THE OWNER DURING THIS COURSE
- 10. THE CONTRACTOR SHALL IDENTIFY ANY NON-FUNCTIONING UTILITY/SYSTEM, PRIOR TO THE START OF WORK TO THE PROJECT ENGINEER. IDENTIFICATION OF SUCH AFTER THE START OF WORK SHALL BE DEEMED AS DISTURBED/DAMAGED BY THE CONTRACTOR AND SHALL BE REPAIRED AT THE EXPENSE OF THE CONTRACTOR.
- 11. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO PROPERLY SUPPORT ANY UTILITY ENCOUNTERED IN THE COURSE OF THIS WORK.
- 12. THE CONTRACTOR SHALL BE RESPONSIBLE TO REPAIR ANY DAMAGE CAUSED BY CONSTRUCTION OF THIS PROJECT AT THE CONTRACTOR'S EXPENSE.
- 13. THE CONTRACTOR SHALL SECURE ALL EXTERIOR WORK AND STAGING AREAS WITH ACCEPTABLE FENCING.
- 14. THE CONTRACTOR SHALL NOT LEAVE THE WORK AREA UNATTENDED FOR ANY REASON, UNLESS SAFETY PARTITIONS, SAFETY FENCING AND COVERING FOR ALL OPEN TRENCHES ARE INSTALLED AND SECURED.
- 15. THE CONTRACTOR SHALL LEAVE THE WORK SITE CLEAN AND SECURED AT THE END OF EACH WORKING DAY. THE WORK SITE SHALL NOT BE LEFT UNATTENDED AT ANY TIME BY THE CONTRACTOR, UNLESS THE WORK AREA IS PROPERLY SECURED BY THE CONTRACTOR.
- 16. THE CONTRACTOR IS ADVISED THAT THEY ARE SOLELY RESPONSIBLE FOR THE SAFETY OF THE WORK SITE AND SHALL TAKE ALL ACTIONS TO ELIMINATE ANY SAFETY HAZARDS THAT SHALL EXIST AND POSE A THREAT OF HARM TO STUDENTS, EMPLOYEES OF THE OWNER, EMPLOYEES OF THE CONTRACTOR OR OTHER(S). IT SHALL BE THE SOLE RESPONSIBILITY OF THE CONTRACTOR TO TAKE IMMEDIATE ACTION TO ALLEVIATE ANY SAFETY HAZARD THAT MAY EXIST WITHOUT DIRECTION FROM THE OWNER OR THEIR DESIGNEE.
- 17. CONTRACTOR SHALL SAW CUT WITH PROPER BLADE ANY ROADS, CURBS AND SIDEWALKS ENCOUNTERED IN THE COURSE OF THIS WORK.
- 18. ALL HOLES SHALL BE CORED DRILLED WITH DIAMOND CORE BITS.
- 19. CONTRACTOR SHALL BE RESPONSIBLE TO REMOVE ANY AND ALL DEBRIS FROM THE SITE DAILY AND DISPOSE OF SAME OFF THE SITE IN ACCORDANCE WITH ALL LOCAL AND STATE REGULATIONS.
- 20. THE CONTRACTOR SHALL MAINTAIN THE WORK SITE IN A NEAT AND CLEAN CONDITION. THE WORK SITE SHALL BE CLEANED DAILY OF CONSTRUCTION DEBRIS
- 21. GRADE AND RE-SEED AREAS DAMAGED BY TRENCHING AND CONSTRUCTION VEHICLES
- 22. GRADING AND RE-SEEDING TO INCLUDE; TOP SOIL, FERTILIZER, SEEDS AND PROTECTIVE BEDDING.
- 23. SUB-GRADE FILL TO BE COMPACTED TO 95% PROCTOR DENSITY
- 24. PROVIDE PROTECTIVE MEASURES FOR ALL TREES. BUSHES AND DECORATIVE SHRUBBERY. CONTRACTOR TO REPLACE ALL VEGETATION DAMAGED DURING CONSTRUCTION AT NO COST TO THE OWNER.

LEGEND










DOVER GREENS UTILITIES ROUTING


ES-00²

TOWN OF DOVER, DUTCHESS COUNTY, NEW YORK ELECTRIAL SITE DETAILS


DLH

ACL 07/17/15 AS SHOWN 15-153 PAGE 3 OF 19





_INDICATES DRAWING SERIES - INDICATES PROJECT PHASE (1, 2, 3, ETC) /-INDICATES GRID AREA ES - _11 EX: ES-111 = PHASE 1 WORK IN GRID #11 ES-211 = PHASE 2 WORK IN GRID #11 ES-311 = PHASE 3 WORK IN GRID #11



LICENSED PROFESSIONAL ENGINEER'S SEAL IS A VIOLATION OF SECTION 7209, SUB-DIVISION 2 OF THE N.Y. STATE EDUCATION LAW.




22 Mulberry St., Suite 2A, Middletown, NY 10940 t 845-343-1481 fx 845-343-4986

181 Church St., Suite 100, Poughkeepsie, NY 12601 t 845-454-9704 fx 855-320-8735 **DOVER GREENS**

www.fellp.com

15**–**153



AS SHOWN


INDICATES DRAWING SERIES

INDICATES PROJECT PHASE (1, 2, 3, ETC)

INDICATES GRID AREA

ES - ___11

EX: ES-111 = PHASE 1 WORK IN GRID #11
ES-211 = PHASE 2 WORK IN GRID #11
ES-311 = PHASE 3 WORK IN GRID #11



UNAUTHORIZED ALTERATION OR ADDITION TO A PLAN BEARING A LICENSED PROFESSIONAL ENGINEER'S SEAL IS A VIOLATION OF SECTION 7209, SUB-DIVISION 2 OF THE N.Y. STATE EDUCATION LAW.

FELLENZER III
ENGINEERING LLP

22 Mulberry St., Suite 2A, Middletown, NY 10940 t 845-343-1481 fx 845-343-4986

181 Church St., Suite 100, Poughkeepsie, NY 12601 t 845-454-9704 fx 855-320-8735

PROJECT

PROJECT

PROJECT

DESIGNED

DATE:

DOVER GREENS
UTILITIES ROUTING
TOWN OF DOVER, DUTCHESS COUNTY, NEW YORK

DRAWING TITLE:

NATURAL GAS SUPPLY — SITE PLAN

DESIGNED BY:
DLH
SAR
ACL
DATE:

07/17/15
AS SHOWN
DOTCHESS COUNTY, NEW TORK


APPROVED BY PIC:
APPROVED BY PM:
APPROVED BY PIC:
JDF

ES-004
PAGE 6 OF 19

Safely: New York

all 811

fore you dig



KEYNOTES


- (1) EXISTING 13.2 KV ABOVE GROUND PRIMARY SUPPLY
- EXISTING 13.2 KV ABOVE GROUND PRIMARY SUPPLY & EXISTING TELECOMMUNICATIONS/CABLE LINE
- 3 EXISTING TELECOMMUNICATIONS/CABLE LINE
- REMOVE EXISTING TELECOMMUNICATIONS LINE AND REPLACE WITH NEW.
- REMOVE EXISTING 13.2 KV PRIMARY OVERHEAD LINE BETWEEN POLE #5 & POLE #8.
- 6 13.2 KV PRIMARY SUPPLY TO NEW UNDERGROUND 13.2 KV SUPPLY. ROUTE TO BUILDINGS 11,46,94,95,118 & 23 AS SHOWN.

BUILDING & PHASE UTILITY LOADS TABLE (PHASE 1)

			ELECTRI	CAL POWER	LIQUID PETR	<u>Oleum gas ta</u>	NK SIZE (QTY)
BLD #	BUILDING DESCRIPTION	SQFT	KVA	WATTS/SQFT	2,000 GAL	1,000 GAL	500 GAL
2	488 SEAT DINING HALL	25000	165	5.61	2		
3	PARTNER ORG OFFICE BUILDING	69000	550	6.78	4		
10	CAMPUS MINISTRY/OFFICE/CLASSROOM		150	7.34	2		
11	DORMITORY	20000	150	6.38		3	
12	DORMITORY	20000	165	7.01		3	
14	WEA — PARTNER ORG OFFICE BUILDING	25000	225	7.65		3	
15	BASEBALL GRANDSTAND	65000	70	0.92	4		
17	PARTNER ORG OFFICE BUILDING	51000	450	7.50	3		
18	DAYCARE FACILITY	16000	120	6.38	1		
19	BUSINESS INCUBATOR/RESEARCH	36000	290	6.85	2		
20	BUSINESS INCUBATOR/RESEARCH	36000	300	7.08	2		
21	PRIMARY SCHOOL	50935	525	8.76	3		
23	UNIVERSITY ADMINISTRATION	24000	200	7.08			
29	BUSINESS INCUBATOR/RESEARCH	30000	250	7.08	2		
30	BUSINESS INCUBATOR/RESEARCH	30000	250	7.08	2		
31	BUSINESS INCUBATOR/RESEARCH	30000	250	7.08	2		
32	BUSINESS INCUBATOR/RESEARCH	30000	250	7.08	2		
33	FAMILY CENTER	10000	85	7.23	2		
35	ASSEMBLY HALL (SMITH HALL)	50000	300	5.10	2		
43	100 SEAT DINNING HALL (ENLARGE)	5000	75	12.75		1	
46	STAFF RESIDENCE	5040	56	9.44		1	
79*	ENTRANCE GUARD OFFICE	500	2	3.40			1
91	STAFF SINGLE FAMILY HOME	2200	23	8.89			1
92	STAFF SINGLE FAMILY HOME	2200	23	8.89			1
93	STAFF SINGLE FAMILY HOME	2400	23	8.15			1
94	STAFF SINGLE FAMILY HOME	2400	25	8.85			1
95	STAFF SINGLE FAMILY HOME	2400	25	8.85			1
107	CHAPEL (THEOLOGY STUDIES)	29000	190	5.57	2		
118	BETHANY HOUSE — RESIDENCE	14000	115	6.98	1		
119	TEMPORARY CONSTRUCTION STORAGE	4000	65	13.81			1
134*	STORAGE SHED	600	2	2.83			1
	TOTALS 705,053 5,369 38 11 8						8

TEMPORARY HEATING FUEL SYSTEM:

- 1. PHASE 1 BUILDINGS SHALL BE HEATED BY TEMPORARY UNDERGROUND LP GAS TANKS UNTIL SUCH TIME THAT THE PERMANENT COMPRESSED NATURAL GAS TANK FARM AND PIPELINE HAVE BEEN CONSTRUCTED, ARE OPERATIONAL TO THAT BUILDING AND ARE AVAILABLE TO BE CUT OVER WITH MINIMAL DISRUPTION TO THE BUILDING.
- 2. AFTER CUTOVER TO THE CNG SYSTEM, THE TEMPORARY TANKS AND APPURTENANCES SHALL BE REMOVED AND DISPOSED OF IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL LAWS.
- 3. UNDERGROUND TANKS SHALL BE LOCATED IN CLOSE PROXIMITY TO THE MECHANICAL ROOM OF EACH BUILDING AS IS PRACTICAL AND THAT MEETS THE ENGINEER'S APPROVAL.
- 4. REGARDLESS OF THE TANK SIZE, ALL ASME TANKS THAT ARE FILLED ON—SITE MUST BE LOCATED SO THAT THE FILLING CONNECTION AND LIQUID LEVEL GAUGE ARE A MINIMUM OF 10 FEET AWAY FROM ANY EXTERNAL SOURCE OF IGNITION (I.E. ANY OPEN FLAME, PILOT LIGHT, WINDOW A/C, COMPRESSOR, ETC), INTAKE TO DIRECT VENTED GAS APPLIANCE OR INTAKE TO A MECHANICAL VENTILATION SYSTEM.
- 5. UNDERGROUND TANKS UP TO 2,000 GALLON LIQUID CAPACITY SHALL BE A MINIMUM OF 10 FEET FROM THE NEAREST BUILDING OR LOT LINE.
- 6. ALL TANKS SHALL HAVE A MINIMUM SEPARATION OF 3 FEET FROM AN AJACENT TANK.



FELLENZER III
ENGINEERING LLP

22 Mulberry St., Suite 2A, Middletown, NY 10940 t 845-343-1481 fx 845-343-4986

181 Church St., Suite 100, Poughkeepsie, NY 12601 t 845-454-9704 fx 855-320-8735

PAGE 7 OF 19

15-153

www.fellp.com

OTA ROCRESS PRIM.


DOVER GREENS
UTILITIES ROUTING
TOWN OF DOVER, DUTCHESS COUNTY, NEW YORK


PHASE 1 — UTILITIES SUPPLY PLAN


DESIGNED BY: DRAWN BY: APPROVED BY PM: APPROVED BY PIC:


AS SHOWN


Call 811 before you dig


























PMH-9 PAD MOUNTED GEAR WITH S&C POWER | SCHEMATIC 'B'

FUSES WITH FUSED PROTECTION. WITH

PROVISIONS FOR TWO (2) TRANSFORMER CONNECTIONS.

CONNECTION

SUBSTATION

CONNECTION

FOR FUTURE

FOR

FUTURE

SUBSTATION

BUILDING

BUILDING

TRANSFORMER(S)

TRANSFORMER(S)

TRANSFORMER(S)

ELECTRICAL TRANSFORMER SCHEDULE DESCRIPTION SYMBOL | KVA RATING <u>X-1-'XX'</u> 13.2 KV/208Y, 3ø, 4W TRANSFORMER. 'XX' DENOTES BUILDING(S) SERVED. <u>X-2-'XX'</u> 13.2 KV/208Y, 3ø, 4W TRANSFORMER. 'XX' DENOTES BUILDING(S) SERVED. 75 <u>X-3-'XX'</u> 13.2 KV/208Y, 3ø, 4W TRANSFORMER. 'XX' DENOTES BUILDING(S) SERVED. <u>X-4-'XX'</u> 13.2 KV/208Y, 3ø, 4W TRANSFORMER. 'XX' DENOTES BUILDING(S) SERVED. 13.2 KV/208Y, 3ø, 4W TRANSFORMER. 'XX' DENOTES BUILDING(S) SERVED.

<u>ES-16</u>

ALL TRANSFORMERS TYPICAL OF SCHNEIDER ELECTRIC, LIQUID FILLED PAD MOUNTED

	FILLED,	PAD MOUNTED.				
REV#	DATE	REMARKS:	ISSUE #	DATE	ISSUED FO	OR:
%" ¼" ½" 0 1" 2" REFERENCE SCALE						

UNAUTHORIZED ALTERATION OR ADDITION TO A PLAN BEARING A LICENSED PROFESSIONAL ENGINEER'S SEAL IS A VIOLATION OF SECTION 7209, SUB-DIVISION 2 OF THE N.Y. STATE EDUCATION LAW.


FELLENZER III ENGINEERING LLP


22 Mulberry St., Suite 2A, Middletown, NY 10940 t 845-343-1481 fx 845-343-4986


181 Church St., Suite 100, Poughkeepsie, NY 12601 t 845-454-9704 fx 855-320-8735

DOVER GREENS UTILITIES ROUTING

TOWN OF DOVER, DUTCHESS COUNTY, NEW YORK SWITCHING LAYOUT & SCHEDULE **ES-130** 07/17/15 AS SHOWN 15-153 PAGE 16 OF 19









- MARSHES, QUICKSAND, ETC. INSTALL WITH AID OF SAND BARREL OR EQUIVALENT INCREASING ABOVE DEPTH IN GROUND BY ONE FOOT.
- 2. FUTURE GRADES. WHERE GRADE IS TO BE LOWERED IN THE NEAR FUTURE SET POLES SO THAT THEY WILL BE IN THE GROUND NOT LESS THAN THE REQUIRED DEPTH AFTER NEW GRADE IS ESTABLISHED.
- 3. SLOPING GROUND INCREASE SETTING DEPTH AS SHOWN IN ABOVE DIAGRAM BY DISTANCE M. (POLE LENGTHS SHALL BE INCREASED WHERE NECESSARY)

TYPICAL POLE SET DETAIL

N.T.S.

18 LINE MATERIAL DA1E3 EXPANDING ANCHOR — FOUR WAY FLUKE TYPE 19 #2 AWG COPPER GROUND CONDUCTOR	LEGEND AND SCHEDULE OF TERMINAL POLE EQUIPMENT					
SYNTHETIC PRODUCTS S-824 PLASTIC TIE FOR USE ON NEMA CLASS "C" PIN TYPE INSULATOR	SYMBOL	MANUFACTURER	CATALOG #	DESCRIPTION		
3	1	McGRAW EDISON	NP9D8	SKY-GLAZE TYPE INSULATOR ANSI CLASS 55-3		
④ OHIO BRASS 93731 GALVANIZED STEEL DEAD END EXT. STRAP, MIN ULTIMATE STRENGTH 10,000 LBS TWO 11/16" HOLES ON 12" CENTERS ⑥ OHIO BRASS 83064 MALLEABLE IRON SUSPENSION CLAMP WITH CLEVIS, CABLE RANGE .312" – .6", ULTIMATE STRENGTH = 16,000 LBS ⑥ PREFORDED LINE PRODUCTS LINE PRODUCTS CE-5259 CLEVIS EYE, MIN. ULTIMATE STRENGTH 20,000 LBS ⑥ JOSLYN J-6556 GIV HOK, 5,6"® JOMETER BOLT WITH WASHESS AND NUT AS REQUIRED, 4" LONG LAG SCREW PILOT POINT TWIST DRIVE ⑨ PREFORMED LINE PRODUCTS LINE PRODUCTS GUY GRIP – A LUMOWELD – 12,500 LB RATE HOLDING STRENGTH 29" LONG LINE PRODUCTS ⑩ OHIO BRASS 42399 DEAD END INSULATOR, ANSI CLASS 52-9, COLOR SKY GLAZE, AL. CAP AND AL. PIN OR REC CAP AND FE. PIN ⑩ COPPERWELD ———— GUY STRAND CAPTED ⑩ JOSLYN J628B SHEAVE WHEEL ⑩ JOSLYN J629B SHEAVE WHEEL ⑩ JOSLYN 650-12 GLASS STRAIN INSULATORS ⑩ LINE MATERIAL WDA2TB ANCHOR ROD - 25,000 LB AVERAGE ULTIMATE STRENGTH TRIPLE STRAND EYE - 1"x 8"-0" ⑩ LINE MATERIAL DA1E3 EXPANDING ANCHOR - FOUR WAY FLUKE TYPE ⑩	2	SYNTHETIC PRODUCTS	S-824	PLASTIC TIE FOR USE ON NEMA CLASS "C" PIN TYPE INSULATOR		
④ OHIO BRASS 93731 CALVANIZED STEEL DEAD END EXT. STRAP, MIN ULTIMATE STRENGTH 10,000 LBS (IN 12" CENTERS) ⑥ OHIO BRASS 83064 MALEABLE IRON SUSPENSION CLAMP WITH CLEVIS, CABLE RANGE .312" − .6", ULTIMATE STRENGTH − 16,000 LBS ⑥ PREFORMED LINE PRODUCTS CE−5259 CLEVIS EYE, MIN. ULTIMATE STRENGTH 20,000 LBS ⑥ JOSLYN J−6556 GLY HOOK, 5/8" DIAMETER BOLT WITH WASHERS AND NUT AS REQUIRED, 4" LONG LAG SCREW PILOT POINT TWIST DRIVE ⑥ PREFORMED LINE PRODUCTS CUY GOR, 5/8" DIAMETER BOLT WITH WASHERS AND NUT AS REQUIRED, 4" LONG LAG SCREW PILOT POINT TWIST DRIVE ⑥ PREFORMED LINE PRODUCTS CUY GOR, 5/8" DIAMETER BOLT WITH WASHERS AND NUT AS REQUIRED, 4" LONG LAG SCREW PILOT POINT TWIST DRIVE ⑥ PREFORMED LINE PRODUCTS CUY GORP A JAUNOWELD -12,500 LB RATE HOLDING STRENGTH 29" LONG -5/26" PAUL PRODUCTS LINE PRODUCTS AL. PIN OR FE. CAP AND FE. PIN ⑥ CHANCE S-1530 GP DEAD END INSULATOR, ANSI CLASS 52-9, COLOR SKY GLAZE, AL. CAP AND AL. PIN OR FE. CAP AND FE. PIN ⑥ JOSLYN J6288 SHEAVE WHEEL ⑥ JOSLYN J6288 SHEAVE WHEEL ⑥ LINE MATERIAL LINE MATERIAL DA1E3 ANCHOR ROD - 25,000 LB AVERAGE ULTIMATE STRENGTH TRIPLE STRAND EYE - 1"x 8"-0" ARCHAR LINE ARCHARD ALL PIN OR ARCHARD ALL PIN OR ARCHARD	_			5/8" DIAMETER BOLT WITH WASHERS AND NUT AS REQUIRED — LENGTH AS REQUIRED		
S.", ULTIMATE STRENGTH — 16,000 LBS		OHIO BRASS	93731			
UINE PRODUCTS OHIO BRASS OHIO BRASS DISTRIBUTION AND TRANSMISSION ANCHOR SHACKLE COMPLETE WITH CLEVIS PIN AND COTTER KEY. MIN. ULTIMATE STRENGTH 25,000 LBS. GUY HOOK, 5/8" DIAMETER BOLT WITH WASHERS AND NUT AS REQUIRED, 4" LONG LAG SCREW PILOT POINT TWIST DRIVE OHIO BRASS O	(5)	OHIO BRASS	83064			
PIN AND COTTER KEY. MIN. ULTIMATE STRENGTH 25,000 LBS. (B) JOSLYN J-6556 GUY HOOK, 5/8" DIAMETER BOLT WITH WASHERS AND NUT AS REQUIRED, 4" LONG LAG SCREW PILOT POINT TWIST DRIVE GUY GIPP - ALUMOWELD - 12,500 LB RATE HOLDING STRENGTH 29" LONG - SIZE FOR GUY STRAND LISTED (D) OHIO BRASS 42399 DEAD END INSULATOR, ANSI CLASS 52-9, COLOR SKY GLAZE, AL. CAP AND AL. PIN OR FE. CAP AND FE. PIN (D) CHANCE S-1530 GP HOT LINE CLAMP (CU AL.) (D) BURNDY GUY STRAND - 10,000 LB ALUMOWELD (E) JOSLYN JESBB SHEAVE WHEEL (E) JOSLYN 650-12 GLASS STRAIN INSULATORS (E) PREFORMED LINE PRODUCTS (D) LINE MATERIAL DA1E3 ANCHOR ROD - 25,000 LB AVERAGE ULTIMATE STRENGTH TRIPLE STRAND EYE - 1"x 8"-0" (E) JOSLYN AC45901 STRAITLINE CLAMP (E) JOSLYN AC45901 STRAITLINE CLAMP (E) JOSLYN AC45901 STRAITLINE CLAMP (E) JOSLYN 24626 STEEL PIN (D) PREFORMED STRAITLINE STRAND ALUMINUM, 1 STRAND STEEL POLY COVERED CONDUCTOR "PIGNUT" (E) JOSLYN AC45901 STRAITLINE CLAMP (E) JOSLYN AC45901 STRAITLINE STRAINDARDS (E) JOSLYN AC45901 STRAITLINE CLAMP (E) JOSLYN AC45901 STRAITLINE STRAINDARDS (E) JOSLYN AC45901 STRAITLINE STRAIN	6		CE-5259	CLEVIS EYE, MIN. ULTIMATE STRENGTH 20,000 LBS		
4" LONG LAG SCREW PILOT POINT TWIST DRIVE (1) PREFORMED LINE PRODUCTS (2) OHIO BRASS 42399 DEAD END INSULATOR, ANSI CLASS 52-9, COLOR SKY GLAZE, AL. CAP AND AL. PIN OR FE. CAP AND FE. PIN (3) CHANCE (4) BURNDY COMPRESSION CONNECTOR SIZE AS REQUIRED. (5) JOSLYN (6) JOSLYN (6) CHANCE (7) GUY STRAND - 10,000 LB ALUMOWELD (8) JOSLYN (9) JOSLYN (10) CHANCE (11) CPEFORMED LINE PRODUCTS (13) LINE MATERIAL (14) DA1E3 EXPANDING ANCHOR FOUR WAY FLUKE TYPE (15) JOSLYN (16) LINE MATERIAL (17) DASLYN (18) LINE MATERIAL (19) CHANCE (10) CHANCE (10	7	OHIO BRASS	13722			
OHIO BRASS 42399 DEAD END INSULATOR, ANSI CLASS 52-9, COLOR SKY GLAZE, AL. CAP AND AL. PIN OR FE. CAP AND FE. PIN CHANCE S-1530 GP HOT LINE CLAMP (CU AL) BURNDY COMPRESSION CONNECTOR SIZE AS REQUIRED. GUY STRAND - 10,000 LB ALUMOWELD SHEAVE WHEEL GUY GUARD LINE MATERIAL DA163 EXPANDING ANCHOR - FOUR WAY FLUKE TYPE LINE MATERIAL DA163 EXPANDING ANCHOR - FOUR WAY FLUKE TYPE AEAC COPPER GROUND CONDUCTOR AERIAL PRIMARY LINE—#2 ACSR 6 STRAND ALUMINUM, 1 STRAND STEEL POLY COVERED CONDUCTOR "PIGNUT" S&C 89022R3-E POLE MOUNT SINGLE PHASE CSP TRANSFORMER. 2 BUSHING, 15KV CLASS PRIMARY, 240 V SECONDARY DYNAVAR DV LIGHTNING ARRESTER 7.62/13.2KV WYE	8	JOSLYN	J-6556			
AL. PIN OR FE. CAP AND FE. PIN CHANCE S-1530 GP HOT LINE CLAMP (CU AL) COMPRESSION CONNECTOR SIZE AS REQUIRED. COPPERWELD GUY STRAND - 10,000 LB ALUMOWELD JOSLYN J6288 SHEAVE WHEEL SHEAVE WHEEL LINE PRODUCTS LINE MATERIAL WDA2T8 ANCHOR ROD - 25,000 LB AVERAGE ULTIMATE STRENGTH TRIPLE STRAND EYE - 1"x 8'-0" LINE MATERIAL DA1E3 EXPANDING ANCHOR - FOUR WAY FLUKE TYPE LINE MATERIAL DA1E3 EXPANDING ANCHOR - FOUR WAY FLUKE TYPE ACCOVERED CONDUCTORS "PIGNUT" JOSLYN AC45901 STRAITLINE CLAMP JOSLYN 24626 STEEL PIN S & C 89022R3-E OPEN CUTOUT TYPE XS 14.4KV RATING AMP. CONT. 100 NEMA STANDARD TYPE 'K' PRIMARY DISTRIBUTION FUSE LINKS SIZE ACCORDING TO ORANGE AND ROCKLAND UTILITIES STANDARDS RTE POLE MOUNT SINGLE PHASE CSP TRANSFORMER. 2 BUSHING, 15KV CLASS PRIMARY, 240 V SECONDARY	9					
BURNDY COMPRESSION CONNECTOR SIZE AS REQUIRED. GOPPERWELD GUY STRAND - 10,000 LB ALUMOWELD JOSLYN J6288 SHEAVE WHEEL GOPPERORMED LINE PRODUCTS LINE MATERIAL WDA2TB ANCHOR ROD - 25,000 LB AVERAGE ULTIMATE STRENGTH TRIPLE STRAND EYE - 1"x 8'-0" LINE MATERIAL DA1E3 EXPANDING ANCHOR - FOUR WAY FLUKE TYPE LINE MATERIAL DA1E3 EXPANDING ANCHOR - FOUR WAY FLUKE TYPE LINE MATERIAL DA1E3 EXPANDING CONDUCTOR CONDUCTOR AERIAL PRIMARY LINE #2 ACSR 6 STRAND ALUMINUM, 1 STRAND STEEL POLY COVERED CONDUCTORS "PIGNUT" JOSLYN AC45901 STRAITLINE CLAMP JOSLYN 24626 STEEL PIN S & C 89022R3-E OPEN CUTOUT TYPE XS 14.4KV RATING AMP. CONT. 100 MEMA STANDARD TYPE 'K' PRIMARY DISTRIBUTION FUSE LINKS SIZE ACCORDING TO ORANGE AND ROCKLAND UTILITIES STANDARDS RTE POLE MOUNT SINGLE PHASE CSP TRANSFORMER. 2 BUSHING, 15KV CLASS PRIMARY, 240 V SECONDARY	10	OHIO BRASS	42399	DEAD END INSULATOR, ANSI CLASS 52-9, COLOR SKY GLAZE, AL. CAP AND AL. PIN OR FE. CAP AND FE. PIN		
GUY STRAND — 10,000 LB ALUMOWELD GUY GUARD GUY GUARD GUY GUARD GUY GUARD GUY GUARD LINE MATERIAL DA1E3 EXPANDING ANCHOR — FOUR WAY FLUKE TYPE GUY GUARD GUY GUARD LINE MATERIAL DA1E3 EXPANDING ANCHOR — FOUR WAY FLUKE TYPE #2 AWG COPPER GROUND CONDUCTOR AERIAL PRIMARY LINE— #2 ACSR 6 STRAND ALUMINUM, 1 STRAND STEEL POLY COVERED CONDUCTORS "PIGNUT" JOSLYN AC45901 STRAITLINE CLAMP JOSLYN AC45901 STRAITLINE CLAMP S& C B9022R3—E OPEN CUTOUT TYPE XS 14.4KV RATING AMP. CONT. 100 PATE ACCORDING TO ORANGE AND ROCKLAND UTILITIES STANDARDS RTE POLE MOUNT SINGLE PHASE CSP TRANSFORMER. 2 BUSHING, 15KV CLASS PRIMARY, 240 V SECONDARY DYNAVAR DV LIGHTNING ARRESTER 7.62/13.2KV WYE	11)	CHANCE	S-1530 GP	HOT LINE CLAMP (CU AL)		
JOSLYN JOSLYN JOSLYN G50-12 GLASS STRAIN INSULATORS PREFORMED LINE PRODUCTS LINE MATERIAL DA1E3 EXPANDING ANCHOR - FOUR WAY FLUKE TYPE LINE MATERIAL DA1E3 EXPANDING ANCHOR - FOUR WAY FLUKE TYPE LINE MATERIAL DA1E3 EXPANDING ANCHOR - FOUR WAY FLUKE TYPE LINE MATERIAL DA1E3 EXPANDING ANCHOR - FOUR WAY FLUKE TYPE JOSLYN AC45901 STRAITLINE CLAMP JOSLYN JOSLYN AC45901 STRAITLINE CLAMP STEEL PIN S & C B9022R3-E OPEN CUTOUT TYPE XS 14.4KV RATING AMP. CONT. 100 PNEMA STANDARD TYPE 'K' PRIMARY DISTRIBUTION FUSE LINKS SIZE ACCORDING TO ORANGE AND ROCKLAND UTILITIES STANDARDS RTE OB 217109-8093 DYNAVAR DV LIGHTNING ARRESTER 7.62/13.2KV WYE	12	BURNDY		COMPRESSION CONNECTOR SIZE AS REQUIRED.		
JOSLYN 650-12 GLASS STRAIN INSULATORS GUY GUARD PREFORMED LINE PRODUCTS LINE MATERIAL DA1E3 EXPANDING ANCHOR - FOUR WAY FLUKE TYPE LINE MATERIAL DA1E3 EXPANDING ANCHOR - FOUR WAY FLUKE TYPE #2 AWG COPPER GROUND CONDUCTOR AERIAL PRIMARY LINE- #2 ACSR 6 STRAND ALUMINUM, 1 STRAND STEEL POLY COVERED CONDUCTORS "PIGNUT" JOSLYN AC45901 STRAITLINE CLAMP JOSLYN AC45901 STRAITLINE CLAMP JOSLYN AC45901 STRAITLINE CLAMP POPEN CUTOUT TYPE XS 14.4KV RATING AMP. CONT. 100 PEN CUTOUT TYPE XS 14.4KV RATING AMP. CONT. 100 RTE RTE NEMA STANDARD TYPE 'K' PRIMARY DISTRIBUTION FUSE LINKS SIZE ACCORDING TO ORANGE AND ROCKLAND UTILITIES STANDARDS RTE POLE MOUNT SINGLE PHASE CSP TRANSFORMER. 2 BUSHING, 15KV CLASS PRIMARY, 240 V SECONDARY DYNAVAR DV LIGHTNING ARRESTER 7.62/13.2KV WYE	13	COPPERWELD		GUY STRAND — 10,000 LB ALUMOWELD		
JOSLYN 650-12 GLASS STRAIN INSULATORS GUY GUARD LINE MATERIAL DA1E3 EXPANDING ANCHOR - FOUR WAY FLUKE TYPE LINE MATERIAL JOSLYN CONDUCTOR AC45901 STRAITLINE CLAMP JOSLYN AC45901 STRAITLINE CLAMP S & C B9022R3-E POLE MOUNT SINGLE PHASE CSP TRANSFORMER. 2 BUSHING, 15kV CLASS PRIMARY, 240 V SECONDARY COB CLASS STRAIN INSULATORS GUY GUARD ANCHOR ROD - 25,000 LB AVERAGE ULTIMATE STRENGTH TRIPLE STRAND EYE - 1"x 8'-0" EXPANDING ANCHOR - FOUR WAY FLUKE TYPE #2 AWG COPPER GROUND CONDUCTOR ACRIAL PRIMARY LINE - #2 ACSR 6 STRAND ALUMINUM, 1 STRAND STEEL POLY COVERED CONDUCTORS "PIGNUT" S & C B9022R3-E OPEN CUTOUT TYPE XS 14.4KV RATING AMP. CONT. 100 NEMA STANDARD TYPE 'K' PRIMARY DISTRIBUTION FUSE LINKS SIZE ACCORDING TO ORANGE AND ROCKLAND UTILITIES STANDARDS RTE OPLE MOUNT SINGLE PHASE CSP TRANSFORMER. 2 BUSHING, 15kV CLASS PRIMARY, 240 V SECONDARY DYNAVAR DV LIGHTNING ARRESTER 7.62/13.2kV WYE	14	JOSLYN	J6288	SHEAVE WHEEL		
LINE PRODUCTS LINE MATERIAL WDA2T8 ANCHOR ROD - 25,000 LB AVERAGE ULTIMATE STRENGTH TRIPLE STRAND EYE - 1"x 8'-0" LINE MATERIAL DA1E3 EXPANDING ANCHOR - FOUR WAY FLUKE TYPE #2 AWG COPPER GROUND CONDUCTOR AERIAL PRIMARY LINE- #2 ACSR 6 STRAND ALUMINUM, 1 STRAND STEEL POLY COVERED CONDUCTORS "PIGNUT" JOSLYN AC45901 STRAITLINE CLAMP JOSLYN S & C 89022R3-E OPEN CUTOUT TYPE XS 14.4KV RATING AMP. CONT. 100 PMA STANDARD TYPE 'K' PRIMARY DISTRIBUTION FUSE LINKS SIZE ACCORDING TO ORANGE AND ROCKLAND UTILITIES STANDARDS RTE OB 217109-8093 DYNAVAR DV LIGHTNING ARRESTER 7.62/13.2KV WYE		JOSLYN	650-12	GLASS STRAIN INSULATORS		
LINE MATERIAL DA1E3 EXPANDING ANCHOR — FOUR WAY FLUKE TYPE 42 AWG COPPER GROUND CONDUCTOR AERIAL PRIMARY LINE— #2 ACSR 6 STRAND ALUMINUM, 1 STRAND STEEL POLY COVERED CONDUCTORS "PIGNUT" JOSLYN AC45901 STRAITLINE CLAMP JOSLYN 24626 STEEL PIN S & C 89022R3—E OPEN CUTOUT TYPE XS 14.4KV RATING AMP. CONT. 100 MEMA STANDARD TYPE 'K' PRIMARY DISTRIBUTION FUSE LINKS SIZE ACCORDING TO ORANGE AND ROCKLAND UTILITIES STANDARDS RTE ——— POLE MOUNT SINGLE PHASE CSP TRANSFORMER. 2 BUSHING, 15KV CLASS PRIMARY, 240 V SECONDARY OB 217109—8093 DYNAVAR DV LIGHTNING ARRESTER 7.62/13.2KV WYE	16		PG5104	GUY GUARD		
#2 AWG COPPER GROUND CONDUCTOR AERIAL PRIMARY LINE—#2 ACSR 6 STRAND ALUMINUM, 1 STRAND STEEL POLY COVERED CONDUCTORS "PIGNUT" DOSLYN DOSLY DOSL	①	LINE MATERIAL	WDA2T8	ANCHOR ROD - 25,000 LB AVERAGE ULTIMATE STRENGTH TRIPLE STRAND EYE - 1"x 8'-0"		
CONDUCTOR AERIAL PRIMARY LINE—#2 ACSR 6 STRAND ALUMINUM, 1 STRAND STEEL POLY COVERED CONDUCTORS "PIGNUT" DISSLYN AC45901 STRAITLINE CLAMP STRAITLINE CLAMP SEEL PIN SEEL PIN SEEL PIN PEN CUTOUT TYPE XS 14.4KV RATING AMP. CONT. 100 PEN CUTOUT TYPE XS 14.4KV RATING AMP. CONT. 100 REMA STANDARD TYPE 'K' PRIMARY DISTRIBUTION FUSE LINKS SIZE ACCORDING TO ORANGE AND ROCKLAND UTILITIES STANDARDS RTE POLE MOUNT SINGLE PHASE CSP TRANSFORMER. 2 BUSHING, 15KV CLASS PRIMARY, 240 V SECONDARY DYNAVAR DV LIGHTNING ARRESTER 7.62/13.2KV WYE	18	LINE MATERIAL	DA1E3	EXPANDING ANCHOR - FOUR WAY FLUKE TYPE		
CONDUCTORS ACHORDOUT ARRIAL PRIMARY LINE—#2 ACSR 6 STRAND ALUMINUM, 1 STRAND STEEL POLY COVERED CONDUCTORS "PIGNUT" JOSLYN AC45901 STRAITLINE CLAMP STEEL PIN S & C 89022R3—E OPEN CUTOUT TYPE XS 14.4KV RATING AMP. CONT. 100 PHASE ACCORDING TO ORANGE AND ROCKLAND UTILITIES STANDARDS RTE ——— POLE MOUNT SINGLE PHASE CSP TRANSFORMER. 2 BUSHING, 15KV CLASS PRIMARY, 240 V SECONDARY OB 217109—8093 DYNAVAR DV LIGHTNING ARRESTER 7.62/13.2KV WYE	19					
JOSLYN 24626 STEEL PIN S & C 89022R3-E OPEN CUTOUT TYPE XS 14.4KV RATING AMP. CONT. 100 NEMA STANDARD TYPE 'K' PRIMARY DISTRIBUTION FUSE LINKS SIZE ACCORDING TO ORANGE AND ROCKLAND UTILITIES STANDARDS RTE POLE MOUNT SINGLE PHASE CSP TRANSFORMER. 2 BUSHING, 15KV CLASS PRIMARY, 240 V SECONDARY OB 217109-8093 DYNAVAR DV LIGHTNING ARRESTER 7.62/13.2KV WYE	_			AERIAL PRIMARY LINE- #2 ACSR 6 STRAND ALUMINUM, 1 STRAND STEEL POLY		
S & C 89022R3-E OPEN CUTOUT TYPE XS 14.4KV RATING AMP. CONT. 100 NEMA STANDARD TYPE 'K' PRIMARY DISTRIBUTION FUSE LINKS SIZE ACCORDING TO ORANGE AND ROCKLAND UTILITIES STANDARDS RTE POLE MOUNT SINGLE PHASE CSP TRANSFORMER. 2 BUSHING, 15KV CLASS PRIMARY, 240 V SECONDARY OB 217109-8093 DYNAVAR DV LIGHTNING ARRESTER 7.62/13.2KV WYE	2)	JOSLYN	AC45901	STRAITLINE CLAMP		
NEMA STANDARD TYPE 'K' PRIMARY DISTRIBUTION FUSE LINKS SIZE ACCORDING TO ORANGE AND ROCKLAND UTILITIES STANDARDS POLE MOUNT SINGLE PHASE CSP TRANSFORMER. 2 BUSHING, 15KV CLASS PRIMARY, 240 V SECONDARY OB 217109-8093 DYNAVAR DV LIGHTNING ARRESTER 7.62/13.2KV WYE	22	JOSLYN	24626	STEEL PIN		
NEMA STANDARD TYPE 'K' PRIMARY DISTRIBUTION FUSE LINKS SIZE ACCORDING TO ORANGE AND ROCKLAND UTILITIES STANDARDS RTE POLE MOUNT SINGLE PHASE CSP TRANSFORMER. 2 BUSHING, 15KV CLASS PRIMARY, 240 V SECONDARY OB 217109-8093 DYNAVAR DV LIGHTNING ARRESTER 7.62/13.2KV WYE	23	S & C	89022R3-E	OPEN CUTOUT TYPE XS 14.4KV RATING AMP. CONT. 100		
PRIMARY, 240 V SECONDARY OB 217109-8093 DYNAVAR DV LIGHTNING ARRESTER 7.62/13.2KV WYE						
	25	RTE				
	2 6	ОВ	217109-8093	DYNAVAR DV LIGHTNING ARRESTER 7.62/13.2KV WYE		
				GUY ATTACHMENT		





SECTION 7209, SUB-DIVISION 2 OF THE N.Y. STATE EDUCATION LAW.


FELLENZER III ENGINEERING LLP


22 Mulberry St., Suite 2A, Middletown, NY 10940 t 845-343-1481 fx 845-343-4986 181 Church St., Suite 100, Poughkeepsie, NY 12601 t 845-454-9704 fx 855-320-8735

DOVER GREENS UTILITIES ROUTING TOWN OF DOVER, DUTCHESS COUNTY, NEW YORK


PHASE 1 ELECTRIC SUPPLY - SITE DETAILS

ES-701 07/17/15 15-153 AS SHOWN PAGE 17 OF 19







- 5. ALL MATERIAL AND EQUIPMENT TO BE INSTALLED BY ELECTRICAL CONTRACTOR UNLESS OTHERWISE SPECIFIED.
- 6. MIN. AIR SPACE CLEARANCE FOR BARE CONDUCTORS: A)13" BETWEEN PHASE WIRES. B)????" MIN PHASE TO GROUND.
- 7. ALL CABLE CONNECTIONS ARE TO BE COMPRESSION
- 8. INSTALLATION TO CONFORM TO ALL ORANGE AND ROCKLAND UTILITIES STANDARDS.
- 9. WHEN THE INSTALLATION IS WITHIN 10 FEET OF ANOTHER GROUND GRID, THE TWO GROUND GRIDS SHALL BE CONNECTED TOGETHER AS PER NOTES 2 & 3
- 10. A SEPARATE 600 V NEUTRAL (EQUAL IN SIZE TO PHASE CONDUCTORS) MUST BE INSTALLED WITH THE PHASE CONDUCTORS WHEN SHIELDED-JACKETED PRIMARY CABLE IS USED.
- 11. PROVIDE 10 FEET OF EXTRA SLACK IN EACH CABLE COILED IN BOX PAD.
- 12. CABINET TO BE GROUNDED AT ALL FOUR CORNERS.
- 13. ALL GROUNDS TO BE INTERCONNECTED.
- 14. FOLLOW MANUFACTURER'S PRIMARY CABLE TERMINATOR INSTALLATION INSTRUCTIONS EXCEPT FOR STRESS CONE GROUNDING WIRE, USE A SEPARATE #14 BARE CU CONDUCTOR AND CONNECT TO GROUND BUS.




PRIMARY METERING TRANSCLOSURE



COMMON UNTILITY TRENCH CONFIGURATION







t 845-343-1481 fx 845-343-4986


t 845-454-9704 fx 855-320-8735 **DOVER GREENS UTILITIES ROUTING**




TOWN OF DOVER, DUTCHESS COUNTY, NEW YORK SITE UTILITY DETAILS **ES-702** 07/17/15 AS SHOWN 15-153 PAGE 18 OF 19










5. REGARDLESS OF THE TANK SIZE, ALL ASME TANKS THAT ARE FILLED ON-SITE MUST BE LOCATED SO THAT THE FILLING CONNECTION AND LIQUID LEVEL GAUGE ARE A MINIMUM OF 10 FEET AWAY FROM ANY EXTERNAL SOURCE OF IGNITION (I.E. ANY OPEN FLAME, PILOT LIGHT, WINDOW A/C, COMPRESSOR ETC), INTAKE TO DIRECT VENTED GAS APPLIANCE OR INTAKE TO A MECHANICAL DIG SATELY. New York

BACKFILL MATERIAL

SAN-EARTH

UNDERGROUND LIQUID PETROLEUM GAS TANK DETAIL



ISSUED FOR: